

## Fibre optic termination point

# **2LINE Zelos BOX**

The 2LINE Zelos BOX is an optical subscriber connection box for terminating the optical fibre in the home.

All features and functions required for a professional FTTH installation are contained in a small, compact housing.



Technical data	
Dimensions HxWxD [mm]	300x194x64
Weight	0,96 kg
Material	PC / ABS UL94 V0
Colour	RAL 9003
Closure	Self-locking, Torx screw, lead-sealable
Splice protection holder	2x 12x crimp or 2x 6x shrink
Coupling field	12x LC duplex, 12x SC, 12x E2000/LSH, 2LINE ZAF
Temperature range	-40° Celsius up to +80° Celsius
Protection class	IP20 (for external couplings)
	IP54 (for internal couplings)
Impact resistance level	IK07

### **Areas of application**

- As AP (termination point) in single- and multi-family houses
- As a transfer point in the business customer sector



#### **Advantages**

Installation space for 12 couplings

Exchangeable splice holder for storing shrink or crimp splice protectors

Guided cable entry from below with sealing and integrated or additional cable strain relief

#### Scope of delivery

- 1 pc. 2LINE Zelos BOX
- 2 pcs. splice holders á 12x crimp or 6x shrink
- 1 pc. M20 cable gland (Ø7-13mm)
- 1 pc. cable tie
- 2 pcs. M4x10 locking screw Torx
- 12 pcs. blind cover
- 1 pc. assembly instructions
- 1 set of wall fixings (universal plugs and screws)
- Included couplings and pigtails (yellow) according to customer requirements

#### **Optional accessories**

- Couplings and pigtails (yellow)
- Strain relief element 2LINE ZAF
- Lock

Date: 04.2022