

Fibre optic termination point

2LINE Zelos BOX

The 2LINE Zelos BOX is an optical subscriber connection box for terminating the optical fiber in the home.

All features and functions required for a professional FTTH installation are contained in a small, compact housing.



Technical data	
Dimensions HxWxD [mm]	300x194x64
Weight	0,96 kg
Material	PC / ABS UL94 V0
Colour	RAL 9003
Closure	Self-locking, Torx screw, lead-sealable
Splice protection holder	2x 12x crimp or 2x 6x shrink
Coupling field	12x LC duplex, 12x SC, 12x E2000/LSH, 2LINE ZAF
Temperature range	-40° Celsius up to +80° Celsius
Protection class	IP20 (for external couplings) IP54 (for internal couplings)
Impact resistance level	IK07

Areas of application

- As AP (termination point) in single- and multi-family houses
- As a transfer point in the business customer sector

Advantages

- Installation space for 12 couplings
- Exchangeable splice holder for storing shrink or crimp splice protectors
- Guided cable entry from below with sealing and integrated or additional cable strain relief

Scope of delivery

- 1 pc. 2LINE Zelos BOX
- 2 pcs. splice holders á 12x crimp or 6x shrink
- 1 pc. M20 cable gland (Ø7-13mm)
- 1 pc. cable tie
- 2 pcs. M4x10 locking screw Torx
- 12 pcs. blind cover
- 1 pc. assembly instructions
- 1 set of wall fixings (universal plugs and screws)
- Included couplings and pigtails (yellow) according to customer requirements

Optional accessories

- Couplings and pigtails (yellow)
- Strain relief element 2LINE ZAF
- Lock