basic component

Fibre optic handover system

2LINE G-BOX GBT GU

Article no.: 3030354822

For installation in all common ways (street, pavement area or customer plot).

Picture may differ from selected product

Facts

Advantages:

- Sabotage-proof lid closure – can only be opened using special keys
- Suitable for use in high-traffic areas
- Height-adjustable

Scope of delivery:

- includes lid (plastic* or cast)
- *Standard label "2LINE G-BOX": special label possible on request
- 2 pieces of Tri-Head security bolts
- 2 pieces of cover caps for Tri-Head security bolts

Dimensions:

- Overall height: 480 - 580 mm
- Lid dimensions: 157 x 157 mm
- Height adjustment: 100 mm

Properties:

- Corrosion-resistant
- Ready for installation with closing cover
- Dimensions to DIN 3581
- Rattle-proof and maintenance-free
- Sealed ready for installation

Material:

- Cast lid: EN-GJL-250 (GG25)
- Plastic lid: glass fibre reinforced polyamide (PA-GF)
- Top section: glass fibre reinforced polyamide (PA-GF)
- Bottom section: ABS
- Screws: stainless steel V2A (AISI 304L)

Tests/Standards:

- Manufactured in accordance with DIN 3580
- In accordance with DVGW VP310-2
- Verified lid load: 20 metric tons (cast)
- Verified lid load: 12.5 metric tons (plastic)

Features

Variant: GU

Pictures

Accessories required

sealing case

Hauff-Technik GRIDCOM GmbH
Geiselroter Heidle 1
73494 Rosenberg, Germany

Tel.: +49 7967 9008-30
Fax: +49 7967 9008-99

office@hauff-technik-gridcom.de