

# Fibre optic building entry

for buildings without a basement

## GFH30 2x7-10 PRO

For reliable sealing of fibre optic cables.

- **Universal building entry with injection system for drill holes in the most common types of wall**
- **Enables horizontal or oblique installation up to a 45° angle**
- **Low-impact sealing of fibre optic cables by means of sealing lips**



## FACTS

### Material:

- Waterproof concrete stress class 2, Waterproof concrete stress class 1
- Flange and punching pin: ABS
- Ball insert: EPDM
- Sealing tape: butyl
- Corrugated pipe: PE

### Advantages:

- Quick to assemble in just a few minutes
- Not necessary to restore basement seal to DIN 18533

## Scope of delivery:

- 1 piece GFH30
- 1 piece wall terminator element
- 1 piece 2-component resin RESINATOR, 80 ml
- 1 piece mixing nozzle

## Dimensions:

- Area of application: 2 fibre-optic cables with  $\text{Øa}$  7-10 mm or 1 fibre-optic cable with  $\text{Øa}$  6 - 13 mm or 1 fibre-optic cable with  $\text{Øa}$  12 - 16 mm
- for drill holes: ID 30 mm
- For wall thicknesses starting from 200 mm

## FEATURES

Number of cables/medium: 2  
Suitable for medium pipe OD (mm): 7 - 10

## PICTURES

