

Membrane injection system


for buildings without a basement

2LINE MIS25 2x7-10 PRO

Article no.: 3030564551

For reliable sealing of fibre optic cables. For installation in all standard wall types to DIN 18533 W1.1-E, W1.2-E, W2.1-E and waterproof concrete to DIN 1045. Includes 2-component resin RESINATOR.

- **controlled RESINATOR resin discharge thanks to proven membrane injection system**
- **tool-free assembly with RESINATOR double syringe**
- **horizontal or inclined installation up to 45° inclination**



Picture may differ from selected product

Facts

Material:

- Waterproof concrete stress class 2, Waterproof concrete stress class 1
- Membrane sleeve: TPE
- Foil flange: Aluminium-plastic composite foil with butyl rubber
- Wall terminator element: PCFR

Advantages:

- Sealing in all common wall types (DIN 18533/WU concrete)
- Minimum RESINATOR resin quantity thanks to adhesive collar
- Small opening diameter Øi 25 mm
- Quick to assemble in just a few minutes

Scope of delivery:

- 1 piece of 2LINE MIS25
- 1 piece of RESINATOR dual syringe, 25 ml
- 1 piece of wall terminator element

Dimensions:

- for drill holes \varnothing : 25 mm
- for wall thicknesses starting from 150 mm

Features

Number of cables/medium: 2
Suitable for medium pipe OD (mm): 7-10

Pictures

