

Membrane injection system

for buildings without a basement

MIS60S E BL1300 SET1

Article no.: 3030453466

Suitable for sloping entry through the wall or floor slab.

- universal building entry with membrane injection system for sloping drill holes through floor slabs or walls
- controlled ejection of resin through slit membrane hose
- sealing lips ensure gentle seal for media lines



Picture may differ from selected product

Facts

Material:

- Waterproof concrete stress class 2, Waterproof concrete stress class 1
- Flange, seal insert, counter-bearing and adapter: EPDM
- Resin filler hose: PE
- Wall rosette: PE
- Pipe: PVC-U
- Wall terminator element: Flame-retardant polycarbonate

Advantages:

- · Quick to assemble in just a few minutes
- Not necessary to restore basement seal to DIN 18533
- · Variety of pre-mounted seal inserts for variable configuration

Scope of delivery:

- 1 piece of MIS60S
- 1 piece of wall terminator element
- 1 piece of wall rosette
- 10 pieces 2-component resin Resinator, 150 ml

Dimensions:

• For core drills Ø: 62 - 65 mm

• Overall length: 1300 mm

Features

Number of cables/medium: Suitable for medium pipe OD

wall thickness (mm):

1
>1
>1
>1
>4

24-30
>18-24
>12-18
>6-12
>10
>5-7

200 - 1.200

Pictures



Accessories required



Cartridge gun



Quick tensioning device